

ASR & ADR Stainless steel, single and double door enclosures

The **ASR** stainless steel single door wall-mounted enclosure range offers IP 66 protection and comes in various sizes. It prevents water and dust entry, reducing component failure and downtime. Ideal for food, beverage, and pharmaceutical industries, it suits most environments.



- Material: AISI 304L / 316L stainless steel.
- Body: 1.5 mm, folded and seam welded.
- Door: 1.5 mm (304L) or 2 mm (316L), 130° opening, with concealed hinges.
- Sealing: Polyurethane (304L) or silicone (316L) gasket.
- Lock: Customized zamak double-bit 3 mm lock, with anti-vibration mechanism.
- Mounting Plate: 2 mm galvanized steel, adjustable depth.
- Protection: IP 66 | TYPE 4X, 12 | IK 10.
- Finish: 400 pre-grained stainless steel.
- Delivery: Includes door, mounting plate, key, and accessories.

The **ADR** double door wall-mounted stainless steel enclosure range offers IP 55 protection and is ideal for confined spaces. It prevents water and dust entry, reducing component failure and downtime. Suitable for food, beverage, and pharmaceutical industries, it fits most environments.



- Material: AISI 304L / 316L stainless steel.
- Body: 1.5 mm, folded and seam welded.
- Door: 2 mm, 130° opening, with concealed hinges.
- Sealing: Polyurethane (304L) or silicone (316L) gasket.
- Lock: Customized zamak double-bit 3 mm lock, with anti-vibration mechanism.
- Mounting Plate: 2.5 mm galvanized steel, adjustable depth.
- **Protection**: IP 55 | TYPE 12 | IK 10.
- Finish: 400 pre-grained stainless steel.
- **Delivery**: Includes door, mounting plate, key, and accessories.

Product number	Material description (HxWxD) EN
ASR0302015	Wall mounted, 300x200x150, SS304
ASR0302015-316	Wall mounted, 300x200x150, SS316
ASR0403021	Wall mounted, 400x300x210, SS304
ASR0404021	Wall mounted, 400x400x210, SS304
ASR0404021-316	Wall mounted, 400x400x210, SS316
ASR0406021	Wall mounted, 400x600x210, SS304
ASR0406021-316	Wall mounted, 400x600x210, SS316
ASR0505021	Wall mounted, 500x500x210, SS304
ASR0505021-316	Wall mounted, 500x500x210, SS316
ASR0505030	Wall mounted, 500x500x300, SS304
ASR0505030-316	Wall mounted, 500x500x300, SS316
ASR0604021	Wall mounted, 600x400x210, SS304
ASR0606021	Wall mounted, 600x600x210, SS304
ASR0606021-316	Wall mounted, 600x600x210, SS316
ASR0806021	Wall mounted, 800x600x210, SS304
ASR0806021-316	Wall mounted, 800x600x210, SS316
ASR0808030	Wall mounted, 800x800x300, SS304
ASR0808030-316	Wall mounted, 800x800x300, SS316
ASR1008030	Wall mounted, 1000x800x300, SS304
ASR1008030-316	Wall mounted, 1000x800x300, SS316
ASR1208030	Wall mounted, 1200x800x300, SS304
ADR1001030	Wall mounted, 1000x1000x300, SS304
ADR1201030	Wall mounted 1200x1000x300, SS304
ADR1201030-316	Wall mounted, 1200x1000x300, SS316
AWS41-304	Wallmounting brackets, SS AISI304 (4 ea)
AWS41-316	Wall mounting brackets SS AISI316 (4 ea)
DIP210	Depth interior profile, 210 mm
DIP300	Depth interior profile, 300 mm



Fonseenintie 3 00370 Helsinki, Finland Tel: +358 9 540 49444 Email: info@klinkmannautomation.fi